

## TITAN SUPERGEAR SAE 75W-85

High performance gear oil specially designed for synchromesh transmissions.

### Description

TITAN SUPERGEAR 75W-85 is a high performance multipurpose gear oil suitable for modern transmissions requiring a lower viscosity transmission fluid

### Application

TITAN SUPERGEAR 75W-85 is miscible and compatible with conventional gear oils. In order to utilize the full advantages of TITAN SUPERGEAR 75W-85 a full drain and exchange of the fluid is recommended.

### Advantages/Benefits

- Can be used where mineral oil an SAE 75W-85 is required
- Compatible with many elastomers and other sealant mate

- Ensures smooth gear shifting due to the advanced antifoam characteristics as the fluid resists film break
- Suitable for transmissions that may experience shocks or high loads
- Suitable for use where API MT-1 lubricants are unsuitable
- TITAN SUPERGEAR 75W-85 provides fuel consumption benefits over standard gear oils

### Specifications

- API GL-4

### Approvals

### FUCHS Recommendations

### CHARACTERISTICS

Density @ 15 °C	DIN 51757	0.875	Kg/L
Colour	DIN ISO 2049	0.5	ASTM
Flashpoint (COC)	DIN ISO 2592	200	°C
Pour Point	DIN ISO 3016	-42	°C
Dynamic Viscosity	DIN 51398	102,000 (-40°C)	mPas
Kinematic Viscosity @ 40 °C	ASTM D445	80	cSt
Kinematic Viscosity @ 100 °C	ASTM D445	12.5	cSt
Viscosity Index	ASTM D2270	156	N/A

Product Code: 4109  
Last Update: 03/11/2022